

MODEL 型式		LAMP2-45(C)	LAMP2-60(C)	LAMP2-80(C)	LAMP2-110(C)		LAMP2-160(C)		LAMP2-200(C)		LAMP2-250(C)		
		S	S	S	S	H	S	H	S	H	S	H	
Capacity 能力	tf	45	60	80	110		160		200		250		
Stroke 行程	mm	60	60	80	180	110	200	130	250	150	280	170	
Stroke Per Minute 每分鐘行程數	Fixed Speed 定速	S.P.M.	70	50	60	50	70	45	60	35	50	30	40
	Variable Speed 變速		50 ~ 85	40 ~ 75	40 ~ 75	35 ~ 65	50 ~ 100	30 ~ 55	40 ~ 85	25 ~ 45	35 ~ 70	20 ~ 35	25 ~ 55
Tonnage Rating Point 能力發生點	(B.D.C) mm	2.6	2.6	2.6	5		6		7		7		
Die height 模具閉合高度	(D.H.) mm	260	300	300	400	350	450	400	500	450	550	500	
Adjustment Of Slide 滑塊調整量	mm	30	60	60	90		100		110		120		
Area Of Slide 滑塊面積	(L/R x F/R) mm x mm	1350 x 400	1350 x 400	1350 x 400	1360 x 520		1500 x 580		1850 x 650		2100 x 700		
Diameter Of Shank Hole 模孔徑	mm	Ø38.1	Ø38.1	Ø50.8	Ø50.8		Ø50.8		Ø50.8		Ø50.8		
Area Of Bolster 台盤面積	(L/R x F/R) mm x mm	1350 x 440	1390 x 520	1400 x 520	1880 x 680		2040 x 760		2420 x 840		2700 x 920		
Thickness Of Bolster 台盤厚度	mm	90	90	90	155		165		180		180		
Working Height 工作高度	mm	800	800	850	900		900		1000		1100		
Inside Measurement Of Frame 機身內寬	mm	1180	1198	1174	1466		1606		1950		2190		
Main Motor 主馬達	Fixed Speed 定速	E - HP x P	3 x 4	5 x 4	7.5 x 4	10 x 4		15 x 4		20 x 4		25 x 4	
	Variable Speed 變速	VS - HP x P	5 x 4	7.5 x 4	10 x 4	15 x 4		20 x 4		25 x 4		30 x 4	
INVERTER(OPTIONAL) 變頻器(選擇配備)	HP	5HP	7.5HP	10HP	15HP		20HP		25HP		30HP		
Motor For Slide Adjustment 滑塊調整馬達	HP x P	Manual (手動)	Manual (手動)	1HP x 4P	1HP x 4P (S)		1HP x 4P (S)		1HP x 4P		1.5HP x 4P (S)		
Foot Size 腳座尺寸	mm x mm	1350 x 1110	1350 x 1240	1350 x 1390	1736 x 1785		1916 x 1900		2280 x 2220		2550 x 2510		
Position Of Anchor Bolts 基礎螺栓位置	mm x mm	1170 x 870	1170 x 975	1170 x 1115	1496 x 1450		1636 x 1540		1980 x 1795		2250 x 2040		
Floor Space Required 佔地面積	mm x mm	1710 x 1170	1710 x 1335	1710 x 1475	2090 x 1900		2660 x 2400		2630 x 2340		2910 x 2640		
Overall Height 總高度	mm	2260	2535	2730	3090		3300		3820		4270		
Accueacy 精度		CNS 1ST	CNS 1ST	CNS 1ST	CNS 1ST		CNS 1ST		CNS 1ST		CNS 1ST		
Die Cushion (OPTIONAL) (YOKOHAMA AIR SPRING TYPE)	模墊(選擇配備) (YOKOHAMA 氣壓彈簧)												
Capacity At (5kg/cm ²) 能力	tf	-	-	-	4,520 x 2pcs		7,080 x 2pcs		9,600 x 2pcs		12,560 x 2pcs		
Length Of Stroke 行程	mm	-	-	-	80		80		100		110		
Area Of Pad 面積	mm x mm	-	-	-	480 x 340 x 2pcs		560 x 370 x 2pcs		700 x 450 x 2pcs		720 x 470 x 2pcs		
Weight Of machine 機器總重	kg	5,300	7,000	9,000	14,000		19,000		27,000		35,000		

* S : STANDARD 標準 * H : HIGH SPEED 高速

* Specification subject to change without notice * 規格變更並不另行通知 REPRINT 2016 - YEAR 再版 2016 - 年



力勤精密機械工業股份有限公司
LI CHIN (P.M.I.) CO., LTD.
台灣桃園縣觀音工業區建國路3號(328)
No.3, Chien Kuo Road, Guan Yin Industrial District.
Taoyuan Hsien, Taiwan (328) R.O.C.
Tel : (+886-3) 483-2220, 483-3835 URL : www.lichin.com.tw
Fax : (+886-3) 483-3837 Email (Taiwan) : ligscom@ms37.hinet.net



利進(東南亞)有限公司
LI CHIN (S.E.A.) SDN. BHD. (Co 206798-V)
13, Simpang Empat, Jalan Lahat,
31450 Menglembu, Ipoh, Perak, Malaysia
Tel : (605) 282-3644, 282-4645, 282-3476 URL : www.lichin.com.tw
Fax : (605) 282-2801 Email (Malaysia) : lms71117@lichin.com.my