

MODEL 型式	CAPACITY 能力 TON	TABLE AREA 台盤面積 mm	RAM STROKE 行程 mm	OPEN HEIGHT 最大開距 mm	MOTOR 馬達 HP x P	OPERATION SPEED 升降速度			DIE CUSHION CAPACITY 模墊能力 TON	DIE CUSHION AREA 模墊面積 mm	DIE CUSHION STROKE 模墊行程 mm
						UP 上升	DOWN 下降	PRESSING 加壓			
						mm / sec	mm / sec	mm / sec			
LHDP - 5	5	500 x 300	250	300	2 x 4	140	60	15	-	-	-
LHDP - 10	10	500 x 350	250	350	2 x 4	140	60	15	-	-	-
LHDP - 25	25	700 x 600	360	530	5 x 4	140	60	15	-	-	-
LHDP - 35	35	1400 x 800	360	530	7.5 x 4	140	60	15	-	-	-
LHDP - 50	50	1200 x 1200	400	700	10 x 4	140	60	15	-	-	-
LHDP - 75	75	1240 x 1240	400	700	10 x 4	160	100	10	-	-	-
LHDP - 100	100	1000 x 700	600	800	15 x 4	160	100	10	-	-	-
LHDP - 120	120	1115 x 855	600	800	20 x 4	250	250	10	40	555 x 240	250
LHDP - 150	150	1155 x 980	600	800	20 x 4	250	250	10	50	555 x 240	250
LHDP - 200	200	1250 x 800	600	800	20 x 4	250	250	10	75	635 x 635	200

* Specification subject to change without notice * 規格變更並不另行通知 REPRINT 2016 - YEAR 再版 2016 - 年



力勤精密機械工業股份有限公司
 LI CHIN (P.M.I.) CO., LTD.
 台灣桃園縣觀音工業區建國路3號(328)
 No.3, Chien Kuo Road, Guan Yin Industrial District,
 Taoyuan Hsien, Taiwan (328) R.O.C.
 Tel : (+886-3) 483-2220, 483-3835 URL : www.lichin.com.tw
 Fax : (+886-3) 483-3837 Email (Taiwan) : llgscm@ms37.hinet.net



利進(東南亞)有限公司
 LI CHIN (S.E.A.) SDN. BHD. (Co 206798-V)
 13, Simpang Empat, Jalan Lahat,
 31450 Menglembu, Ipoh, Perak, Malaysia
 Tel : (605) 282-3644, 282-4645, 282-3476 URL : www.lichin.com.tw
 Fax : (605) 282-2801 Email (Malaysia) : lms71117@lichin.com.my